


# MULTIMAX MP 515

<b>TIRE SIZE</b>	<b>445/65 R 22.5 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VEHICUL UNIVERSAL / CAMION PENTRU ÎNGRĂȘĂMINTE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 G



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	444	<b>RIM REC</b>	13
<b>OD (MM)</b>	1150	<b>RIM ALT</b>	14
<b>SLR (MM)</b>	527	<b>ECE</b>	E11-54R-0017868
<b>RC (MM)</b>	3532		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5	4.0	4.5	6.0
90	1740	2060	2410	2750	3075	3390	3800	4500
65	1890	2235	2615	2985	3340	3675	4000	4885
40	2005	2365	2770	3165	3540	3900	4240	5175

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.