

# FLOTATION 648

|                     |   |
|---------------------|---|
|                     | <b>500/50 - 22.5</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | BALYA MAKINESI / BIÇERDÖVER /<br>YAYICI / BIÇERDÖVER / UYGULAMALI<br>MAKINE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
|                     | 151 A8/147 B  |
|                     | 163 A8/159 B  |



## UNDEFINED US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94037827 | <b>RC (IN)</b> | 126.0           |
| <b>SW (IN)</b>  | 19.7     | <b>RIM REC</b> | AG 16.00        |
| <b>OD (IN)</b>  | 42.1     | <b>ECE</b>     | E11-106R-003400 |
| <b>SLR (IN)</b> | 18.7     | <b>PR</b>      | 20              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 49    | 52    | 55    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 14110 | 14580 | 15050 |
| <b>10 FR</b> | 12700 | 13130 | 13550 |
| <b>20 FR</b> | 11290 | 11660 | 12040 |
| <b>25 FR</b> | 10070 | 10420 | 10750 |
| <b>30 FR</b> | 9070  | 9380  | 9640  |
| <b>5 DW</b>  | 9990  | 10330 | 10650 |
| <b>10 DW</b> | 8980  | 9290  | 9580  |
| <b>20 DW</b> | 7990  | 8260  | 8520  |
| <b>25 DW</b> | 7130  | 7370  | 7610  |
| <b>30 DW</b> | 6420  | 6640  | 6780  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.