


# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/80 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	176 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1835	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	838	<b>ECE</b>	E11-106R-009072
<b>RC (MM)</b>	5572	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.2	1.4	1.6	1.8	2	2.2	2.4	2.6	2.8	3	3.2	3.4	3.6
<b>70</b>	3675	4070	4465	4660	4925	5055	5185	5450	5715	5910	6170	6370	6565
<b>FROM 65 TO 40</b>	3975	4405	4825	5040	5325	5470	5610	5890	6180	6390	6675	6890	7100
<b>30</b>	4055	4495	4925	5145	5435	5580	5725	6010	6305	6525	6810	7030	7245
<b>20</b>	4135	4580	5020	5245	5540	5690	5835	6130	6425	6650	6940	7165	7385
<b>10*</b>	4375	4845	5310	5545	5860	6015	6170	6480	6795	7030	7340	7575	7810
<b>UPTO 30 CYCLIC</b>	4515	5000	5480	5720	6045	6210	6370	6690	7015	7255	7575	7820	8060
<b>UPTO 15 CYCLIC</b>	5390	5970	6540	6830	7220	7410	7605	7985	8375	8665	9045	9335	9625
<b>UPTO 10 CYCLIC</b>	5965	6605	7240	7565	7995	8205	8415	8840	9270	9590	10015	10335	10655

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.