


RIDEMAX IT 696

| | |
|---------------------|--|
| TIRE SIZE | 400/80 R 24 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 A8 ; 144 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 404 | RIM REC | DW 13 |
| OD (MM) | 1250 | RIM ALT | W 12; W 14 L |
| SLR (MM) | 558 | ECE | E4-106R-002400 |
| RC (MM) | 3760 | SRI | 600 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 1315 | 1625 | 1905 | 2210 | 2490 | 2800 |
| 50 | 1440 | 1775 | 2080 | 2415 | 2725 | 3060 |
| 40 | 1530 | 1885 | 2210 | 2570 | 2895 | 3250 |
| 30 | 1590 | 1960 | 2300 | 2670 | 3010 | 3380 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.