


AGRIMAX V- FLECTO



TIRE SIZE	VF 600/70 R 30
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	168 D

DIMENSIONS US STANDARD

USA CODE	94064601	RC (IN)	185.5
SW (IN)	23.7	RIM REC	DW 21 B
OD (IN)	63.1	RIM ALT	DW 20 B
SLR (IN)	27.6	ECE	E11-106R-006162

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	5610	6500	7410	8420	9310	10220	11230
FROM 40 TO 25	6170	7150	8150	9260	10240	11230	12350
20	6290	7290	8300	9440	10440	11450	12590
12	6420	7430	8470	9620	10650	11670	12830
5	6790	7860	8950	10180	11250	12350	13580
*UPTO 5 CYC WITH FRONT LOADER	8640	10010	11400	12960	14330	15720	17280
5 HT	6290	7290	8300	9440	10440	11450	12590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.