

# AT 603

<b>TIRE SIZE</b>	<b>10.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / BACKHOE LOADER / IMPLEMENTS / BACKHOE LOADER
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	119 A8
<b>LI/SS FREE ROLLING</b>	131 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	274	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	907	<b>RIM ALT</b>	W 8; 9
<b>SLR (MM)</b>	422	<b>ECE</b>	E11-106R-004546
<b>RC (MM)</b>	2727	<b>PR</b>	10

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.70
10 FR	2730
25 FR	2320
30 FR	2185
40 FR	1950
10 DW	1905
25 DW	1620
30 DW	1525
40 DW	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.