

FLOTATION 648

TIRE SIZE	500/55 - 20
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	ENFARDADEIRA DE FENO / CEIFEIRA / ESPALHADOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	138 A8/134 B
LI/SS FREE ROLLING	150 A8/146 B



DIMENSÕES US STANDARD

CÓDIGO USA	94039234	RC (IN)	124.1
SW (IN)	20.0	RIM REC	16.00
OD (IN)	41.7	ECE	E11-106R-003369
SLR (IN)	18.0	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	29	32	35
5 FR	9290	9830	10340
10 FR	8370	8850	9300
20 FR	7430	7860	8270
25 FR	6640	7020	7390
30 FR	5970	6320	6610
5 DW	6550	6930	7290
10 DW	5890	6240	6560
20 DW	5240	5540	5830
25 DW	4670	4950	5200
30 DW	4210	4450	4670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.