


AGRIMAX FORCE

TIRE SIZE	IF 620/75 R 30
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	169 D



DIMENSIONER IS STANDARD

SW (MM)	650	RIM REC	DW 23 B
OD (MM)	1703	RIM ALT	DW 21 B
SLR (MM)	759	ECE	E11-106R-006496
RC (MM)	5100	SRI	800

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2475	2845	3270	3690	4110	4535	4955	5275
FROM 65 TO 40	2725	3130	3595	4060	4520	4985	5450	5800
30	2830	3288	3735	4220	4700	5180	5665	6030
20	2940	3380	3880	4380	4880	5380	5885	6260
10	3460	3975	4565	5155	5740	6330	6920	7365
UPTO 30 CYC	3540	4065	4670	5275	5875	6480	7085	7540
UPTO 15 CYC	4220	4850	5570	6290	7005	7725	8445	8990
UPTO 10 CYC	4630	5320	6110	6900	7680	8470	9265	9860
10 HT	2830	3255	3735	4220	4700	5180	5665	6030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.