


# TR 135

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>8.3 - 32</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRACTOR / TRAILER  |
| <b>VERSION</b>      | STANDARD   |
| <b>TYRE TYPE</b>    | TT   |
| <b>LI/SS</b>        | 105 A6   |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 211  | <b>RIM REC</b> | W 7            |
| <b>OD (MM)</b>  | 1195 | <b>RIM ALT</b> | W 6            |
| <b>SLR (MM)</b> | 572  | <b>ECE</b>     | E4-106R-002030 |
| <b>RC (MM)</b>  | 3585 | <b>PR</b>      | 6              |

## LOAD CAPACITY (KG/TYRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>2.40</b> |
| 30                | 925         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.