

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 280/85 R 24 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 115 A8/B |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94021536 | RC (IN) | 126.9 |
| SW (IN) | 11.5 | RIM REC | W 10 |
| OD (IN) | 42.8 | RIM ALT | W 9 |
| SLR (IN) | 19.4 | ECE | E4-106R-000611 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 30 | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| 25 | 1480 | 1720 | 1960 | 2200 | 2450 | 2680 |
| 20 | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |
| 5 LT | 1980 | 2300 | 2620 | 2950 | 3270 | 3590 |
| 5 HT | 1590 | 1850 | 2110 | 2370 | 2620 | 2880 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.