


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 480/60 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	145 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94060740	<b>RC (IN)</b>	149.9
<b>SW (IN)</b>	18.5	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	50.8	<b>RIM ALT</b>	W 16 L
<b>SLR (IN)</b>	22.5	<b>ECE</b>	E11-106R-005496

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	3200	3710	4230	4760	5280	5810
<b>FROM 40 TO 25</b>	3520	4090	4660	5240	5810	6395
20	3580	4170	4750	5330	5920	6510
12	3650	4240	4840	5450	6040	6650
5	3860	4500	5130	5750	6380	7030
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	4920	5720	6530	7330	8120	8950
5 HT	3580	4170	4750	5330	5920	6510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.