DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 44

TIRE SIZE	**325/95 R 24**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	CAMIÃO BASCULANTE
VERSÃO	STANDARD
TIRE TYPE	TT
LI/SS	158 B

DIMENSÕES IS STANDARD

OD (MM)	1250	**RIM ALT**	9.00V
SLR (MM)	575	**TRA CODE**	E4
RC (MM)	3790	**STAR RATING**	★★★
RIM REC	8.50V		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.50	4.75	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	3075	3150	3350	3450	3550	3650	3750	3875	4000	4125	4250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..