


# EARTHMAX SR 45 M

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>18.00 R 33</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | TOMBEREAU RIGIDE   |
| <b>VERSION</b>      | STANDARD COMPOUND  |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 195 B  |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>CODE USA</b> | 94513901 | <b>RIM REC</b>     | 13.00/2.5 |
| <b>OD (IN)</b>  | 73.6     | <b>TRA CODE</b>    | E4        |
| <b>SLR (IN)</b> | 33.7     | <b>STAR RATING</b> | ★★★       |
| <b>RC (IN)</b>  | 220.8    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 105   | 109   | 112   | 116   |
|-----------|-------|-------|-------|-------|
| 30        | 24700 | 25400 | 26000 | 26800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.