


AGRIMAX RT 855

TIRE SIZE	320/85 R 34
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI
VERSIONE	STANDARD
TIRE TYPE	TL
LI/SS	141 A8/B



DIMENSIONI IS STANDARD

SW (MM)	329	RIM REC	W 11
OD (MM)	1408	RIM ALT	W 9; W 10
SLR (MM)	645	ECE	E4-106R-001395
RC (MM)	4280	SRI	675

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	930	1085	1420	1730	1880	2010	2190	2370	2575
40	930	1085	1420	1730	1880	2010	2190	2370	2575
30	995	1160	1520	1850	2015	2155	2350	2540	2760
10 LT	1245	1455	1905	2315	2525	2695	2940	3180	3455
10 HT	995	1160	1520	1850	2015	2155	2350	2540	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.