

AW 702

| | |
|---------------------------|---|
| TIRE SIZE | 10.0/80 - 12 |
| UM | US STANDARD |
| CONSTRUCTION | ❖ BIAS |
| MACHINERY | PRESSA PER BALLE DI FIENO / ATTREZZI AGRICOLI / RIMORCHIO / MIETITREBBIA / ATTREZZI AGRICOLI / RIMORCHIO |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS FREE ROLLING | 121 A8 |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94009176 | RC (IN) | 84.4 |
| SW (IN) | 10.4 | RIM REC | 9.00 |
| OD (IN) | 28.0 | RIM ALT | 7.0 |
| SLR (IN) | 12.5 | ECE | E4-106R-002662 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 57 |
|------------------|-----------|
| 5 FR | 4480 |
| 15 FR | 3800 |
| 20 FR | 3580 |
| 25 FR | 3200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.