


AGRIMAX V- FLECTO



TIRE SIZE	VF 710/70 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRATOR DE ALTA POTENCIA / TRATOR
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	185 D

DIMENSÕES US STANDARD

CÓDIGO USA	94066148	RC (IN)	243.4
SW (IN)	28.1	RIM REC	DW 25 B
OD (IN)	81.1	RIM ALT	DW 23 B; DW 24 B
SLR (IN)	36.3	ECE	E11-106R-0010959

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8730	10020	11510	13000	14470	15960	17450	18550
FROM 40 TO 25	9590	11010	12640	14270	15910	17540	19170	20390
20	9780	11230	12900	14560	16230	17890	19550	20800
12	9980	11450	13150	14850	16540	18240	19940	21210
5	10550	12110	13910	15710	17500	19300	21090	22430
*UPTO 5 CYC WITH FRONT LOADER	13430	15420	17700	19980	22280	24560	26840	28550
5 HT	9780	11230	12900	14560	16230	17890	19550	20800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.