


AGRIMAX RT 657

| | |
|---------------------|--|
| TIRE SIZE | 600/65 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 159 D ; 162 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|----------------|
| SW (MM) | 611 | RIM REC | DW 20 B |
| OD (MM) | 1745 | RIM ALT | W 18 L |
| SLR (MM) | 790 | ECE | E4-106R-000623 |
| RC (MM) | 5247 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|--------------|------|------|------|------|------|------|------|------|
| 65 | 2100 | 2450 | 2760 | 3065 | 3370 | 3635 | 4025 | 4375 |
| 50 | 2210 | 2575 | 2895 | 3220 | 3540 | 3815 | 4230 | 4595 |
| 40 | 2280 | 2660 | 2995 | 3325 | 3660 | 3945 | 4370 | 4750 |
| 30 | 2420 | 2820 | 3175 | 3525 | 3880 | 4180 | 4635 | 5035 |
| 10 LT | 2820 | 3285 | 3695 | 4110 | 4520 | 4870 | 5400 | 5865 |
| 10 HT | 2420 | 2820 | 3175 | 3525 | 3880 | 4180 | 4635 | 5035 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.