


AGRIMAX RT 765M

| | |
|---------------------|--|
| TIRE SIZE | 710/70 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D ; 178 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|-----------------|-----------------|
| USA CODE | 94066797 | RC (IN) | 226.4 |
| SW (IN) | 28.2 | RIM REC | DW 23 B |
| OD (IN) | 77.1 | ECE | E11-106R-004072 |
| SLR (IN) | 33.8 | TRA CODE | R1W |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|
| 40 | 6380 | 7330 | 8410 | 9490 | 10580 | 11660 | 12750 | 13560 |
| 30 | 6700 | 7690 | 8840 | 9980 | 11110 | 12260 | 13390 | 14240 |
| 25 | 6940 | 7980 | 9160 | 10340 | 11530 | 12710 | 13890 | 14770 |
| 20 | 7340 | 8430 | 9680 | 10920 | 12170 | 13410 | 14670 | 15600 |
| 5 LT | 8550 | 9820 | 11280 | 12730 | 14190 | 15640 | 17100 | 18180 |
| 5 HT | 7340 | 8430 | 9680 | 10920 | 12170 | 13410 | 14670 | 15600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.