


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 710/60 R 30</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 D



## ABMESSUNGEN US STANDARD

<b>USA-CODE</b>	94513505	<b>RC (IN)</b>	189.0
<b>SW (IN)</b>	28.3	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	64.0	<b>RIM ALT</b>	DW 24 B; DW 27 B
<b>SLR (IN)</b>	27.6	<b>ECE</b>	E11-106R-0010832

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
45	6040	7020	8130	9130	10110	11100	12330
<b>FROM 40 TO 25</b>	6640	7730	8940	10030	11110	12200	13560
20	6770	7870	9120	10220	11330	12430	13820
12	6900	8040	9300	10430	11550	12690	14100
5	7300	8500	9830	11030	12220	13410	14910
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9290	10810	12520	14040	15560	17070	18980
5 HT	6770	7870	9120	10220	11330	12430	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.