


# AGRIMAX RT 765

<b>TYRE SIZE</b>	<b>620/70 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	173 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	625	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1935	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	876	<b>ECE</b>	E11-106R-005833
<b>RC (MM)</b>	5804	<b>SRI</b>	925

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>65</b>	2535	2990	3445	3835	4290	4680	5135	5525	6045	6500
<b>50</b>	2665	3140	3620	4030	4505	4915	5395	5805	6350	6825
<b>40</b>	2780	3280	3775	4205	4700	5130	5625	6055	6625	7120
<b>30</b>	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475
<b>10 LT</b>	3400	4010	4620	5140	5750	6275	6885	7405	8105	8710
<b>10 HT</b>	2920	3440	3965	4415	4935	5385	5910	6355	6955	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.