

# RIDEMAX IT 696

**440/80 R 24 IND****UM** IS STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** TRAKTÖR**VERSION** STANDARD**TIRE TYPE** TL

154 A8 ; 149 D



## UNDEFINED IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 441  | <b>RIM REC</b> | DW 14 L         |
| <b>OD (MM)</b>  | 1314 | <b>RIM ALT</b> | DW 15 L ; DW 13 |
| <b>SLR (MM)</b> | 590  | <b>ECE</b>     | E11-106R-004760 |
| <b>RC (MM)</b>  | 3939 | <b>SRI</b>     | 625             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  |
|------------|------|------|------|------|------|------|
| 65         | 1530 | 1885 | 2210 | 2570 | 2895 | 3250 |
| 50         | 1650 | 2035 | 2385 | 2775 | 3125 | 3510 |
| 40         | 1765 | 2175 | 2550 | 2965 | 3340 | 3750 |
| 30         | 2115 | 2610 | 3060 | 3555 | 4005 | 4500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.