


MULTIMAX MP 522

TIRE SIZE	500/70 R 24 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	164 A8/B



DIMENSÕES US STANDARD

CÓDIGO USA	94032686	RC (IN)	155.1
SW (IN)	19.8	RIM REC	DW 16 L
OD (IN)	51.6	RIM ALT	DW 15 L; DW 18 L
SLR (IN)	23.4	ECE	E4-106R-002395

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	5290	6280	7160	8160	9150	9810	11020	-	-
25	5290	6280	7160	8160	9150	9810	11020	-	-
20	5670	6720	7670	8730	9800	10500	11790	-	-
15	5870	6980	7960	9060	10160	10890	12230	-	-
5 CYC	6450	7940	9350	10750	12230	13320	15050	15870	16530
STATIC	9890	12170	14330	16480	18760	20410	23070	24340	25350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.