


RIDEMAX FL 690

| | |
|---------------------|--|
| TYRE SIZE | 28L R 26 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAILER / IMPLEMENTS / TRAILER |
| VERSION | STANDARD |
| TYRE TYPE | TL |
| LI/SS | 176 A8 ; 173 B |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 719 | RIM REC | DW 25 B |
| OD (MM) | 1590 | RIM ALT | DW 23 B |
| SLR (MM) | 695 | ECE | E11-106R-002985 |
| RC (MM) | 4745 | SRI | 750 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 0.8 | 1.0 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 |
|------------|------|------|------|------|------|------|------|
| 50 | 3120 | 3560 | 4325 | 4680 | 5330 | 5915 | 6500 |
| 40 | 3410 | 3885 | 4725 | 5115 | 5825 | 6465 | 7100 |
| 30 | 3820 | 4355 | 5295 | 5730 | 6525 | 7240 | 7955 |
| 25 | 4060 | 4625 | 5620 | 6085 | 6930 | 7690 | 8450 |
| 10 | 4775 | 5440 | 6615 | 7160 | 8155 | 9050 | 9940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.