


# CON STAR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>440/80 - 24</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS             |
| <b>MACHINERY</b>    | CHARGEUSE COMPACTE / CHARGEUSE<br>TÉLESCOPIQUE / CHARGEUSE<br>COMPACTE / CHARGEUSE<br>TÉLESCOPIQUE |
| <b>VERSION</b>      | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 168 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                         |
|-----------------|----------|----------------|-------------------------|
| <b>CODE USA</b> | 94042067 | <b>RC (IN)</b> | 156.9                   |
| <b>SW (IN)</b>  | 17.9     | <b>RIM REC</b> | DW 14 L                 |
| <b>OD (IN)</b>  | 51.8     | <b>RIM ALT</b> | DW 13; DW 13 L; DW 15 L |
| <b>SLR (IN)</b> | 24.0     | <b>ECE</b>     | E11-106R-003027         |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>73</b> |
| 25               | 12350     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.