



IS standard



GROWING TOGETHER

# AGRIMAX

RADIAL TRACTOR TIRES

## RI 818



PRODUCT DATA SHEET



Radial



154

Performance



Self-Cleaning



Traction



# AGRIMAX RI 818

RADIAL TRACTOR TIRES

🇬🇧 AGRIMAX RI 818 is a radial tire, which has been specifically developed for irrigation applications with pivot irrigators. Its specially designed tread pattern provides excellent traction in wet and muddy conditions in addition to outstanding self-cleaning properties.

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 24"	280/85 R 24 (11.2 R 24)	140	W 10	W 9	287	1086	490	3271	525	STD
Ø 38"	320/85 R 38 (12.4 R 38)	154	W 10	W 9; W 11	319	1509	691	4565	725	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index