



Latest update  
2-06-2026

## DATA SHEET

# EM 936

|                     |                    |
|---------------------|--------------------|
| <b>TYRE SIZE</b>    | <b>16.0/70 -24</b> |
| <b>UM</b>           | US STANDARD        |
| <b>CONSTRUCTION</b> | ⊠ BIAS             |
| <b>MACHINERY</b>    | TELEHANDLER        |
| <b>VERSION</b>      | STANDARD           |
| <b>TL/TT</b>        | TL                 |
| <b>LI/SS</b>        | 143 B ; 162 A2     |



### DIMENSIONS US STANDARD

|                 |          |                 |         |
|-----------------|----------|-----------------|---------|
| <b>USA CODE</b> | 94005352 | <b>RIM REC</b>  | 13 SDC  |
| <b>OD (IN)</b>  | 46.1     | <b>RIM ALT</b>  | 13 (DC) |
| <b>SLR (IN)</b> | 22.6     | <b>PR</b>       | 10      |
| <b>RC (IN)</b>  | 141.7    | <b>TRA CODE</b> | E2      |

### LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 36   | 46    |
|-----------|------|-------|
| 30        | 6010 | -     |
| 5         | -    | 10470 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.