


EARTHMAX SR 22 AS

TIRE SIZE	20.5 R 25
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ПОГРУЗЧИК / ГРЕЙДЕР
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	177 B ; 161 A8 ; 193 A2



РАЗМЕРЫ US STANDARD

USA CODE	94073160	RIM REC	17.00/2.0
OD (IN)	58.8	TRA CODE	E2/G2/L2
SLR (IN)	25.2	STAR RATING	★★/★/★★
RC (IN)	170.2		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91
30	-	-	-	-	-	-	-	-	12800	13600	14300	14800	15200	16100	-	-	-	-
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	21500	22000	22700	24000	24700
MPH / PSI	94																	
30	-																	
25	-																	
5	25400																	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.