


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>710/70 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8/B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	2019	<b>RIM ALT</b>	DW 25 B
<b>SLR (MM)</b>	915	<b>ECE</b>	E11-106R-004896
<b>RC (MM)</b>	6103	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
40	2775	3225	3675	4200	4650	5100	5625	5925	6525	7050	7500
30	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025
10 LT	3720	4325	4925	5630	6235	6835	7540	7940	8745	9450	10050
10 HT	2970	3455	3935	4495	4980	5460	6020	6340	6985	7545	8025

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.