

# AS 504

<b>TYRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94018604	<b>RC (IN)</b>	94.6
<b>SW (IN)</b>	10.4	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	30.9	<b>ECE</b>	E4-106R-001823
<b>SLR (IN)</b>	14.2	<b>PR</b>	18

## LOAD CAPACITY (LBS/TYRE)

<b>MPH / PSI</b>	<b>103</b>
<b>5 FR</b>	6720
<b>15 FR</b>	5720
<b>20 FR</b>	5380
<b>25 FR</b>	4810
<b>5 DW</b>	4780
<b>15 DW</b>	4070
<b>20 DW</b>	3820
<b>25 DW</b>	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.