


# AGRIMAX FORCE



<b>TYRE SIZE</b>	<b>IF 900/60 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	186 D

## DIMENSIONS US STANDARD

<b>USA CODE</b>	94022236	<b>RC (IN)</b>	252.6
<b>SW (IN)</b>	36.1	<b>RIM REC</b>	DW 30 B
<b>OD (IN)</b>	84.5	<b>RIM ALT</b>	TW 30 B
<b>SLR (IN)</b>	37.4	<b>ECE</b>	E11-106R-006494

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	8760	10100	11620	12950	14480	15820	17710	19060
<b>FROM 40 TO 25</b>	9630	11100	12780	14240	15920	17380	19480	20900
20	10010	11540	13280	14800	16540	18080	20250	21780
12	10390	11980	13790	15380	17180	18770	21030	22620
5	12220	14090	16210	18080	20200	22070	24730	26600
<b>UPTO 20 CYC</b>	12520	14430	16600	18510	20690	22600	25320	27230
<b>UPTO 10 CYC</b>	14920	17200	19800	22070	24670	26940	30180	32460
<b>UPTO 5 CYC</b>	16370	18860	21710	24210	27050	29540	33100	35600
5HT	10010	11540	13280	14800	16540	18080	20250	21780

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.