


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>600/65 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MACHINE À VENDANGER / TRACTEUR / MOISSONNEUSE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	159 D ; 162 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94066612	<b>RC (IN)</b>	206.6
<b>SW (IN)</b>	24.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	68.7	<b>RIM ALT</b>	W 18 L
<b>SLR (IN)</b>	31.1	<b>ECE</b>	E4-106R-000623

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4630	5400	6080	6760	7430	8010	8870	9650
30	4870	5680	6380	7100	7800	8410	9330	10130
25	5030	5860	6600	7330	8070	8700	9630	10470
20	5330	6220	7000	7770	8550	9210	10220	11100
5 LT	6220	7240	8150	9060	9960	10740	11900	12930
5 HT	5330	6220	7000	7770	8550	9210	10220	11100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.