


AGRIMAX RT 955

| | |
|---------------------|--|
| TIRE SIZE | 340/85 R 48 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / SKÖRDEMASKIN / ARBETSFORDON |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 151 D ; 154 A8 |



DIMENSIONER US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94059287 | RC (IN) | 219.4 |
| SW (IN) | 13.9 | RIM REC | W 12 |
| OD (IN) | 70.7 | RIM ALT | W 11 |
| SLR (IN) | 33.7 | ECE | E11-106R-005765 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 64 |
|-----------|------|------|------|------|------|------|------|------|------|-------|-------|
| 40 | 3270 | 3660 | 4110 | 4500 | 4950 | 5260 | 5790 | 6240 | 6620 | 7000 | 7610 |
| 30 | 3440 | 3840 | 4320 | 4720 | 5200 | 5520 | 6070 | 6560 | 6960 | 7350 | 7990 |
| 25 | 3560 | 3970 | 4460 | 4880 | 5380 | 5710 | 6280 | 6780 | 7200 | 7610 | 8270 |
| 20 | 3770 | 4210 | 4730 | 5170 | 5700 | 6040 | 6660 | 7190 | 7620 | 8060 | 870 |
| 5 | 4920 | 5480 | 6160 | 6730 | 7420 | 7880 | 8670 | 9360 | 9930 | 10500 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.