

# AS 504

**11.0/65 - 12****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TT

101 A8

114 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94019427	<b>RC (IN)</b>	81.6
<b>SW (IN)</b>	10.7	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	27.6	<b>ECE</b>	E4-106R-002834
<b>SLR (IN)</b>	12.6	<b>PR</b>	8

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>42</b>
<b>5 FR</b>	3640
<b>15 FR</b>	3100
<b>20 FR</b>	2910
<b>25 FR</b>	2600
<b>5 DW</b>	2550
<b>15 DW</b>	2160
<b>20 DW</b>	2040
<b>25 DW</b>	1820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.