


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>250/85 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR / LANDWIRTSCHAFTLICHE GERÄTE / TRAUBENERNTEMASCHINE / ERNTEMASCHINE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	109 A8/B



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	251	<b>RIM REC</b>	W 8
<b>OD (MM)</b>	1036	<b>RIM ALT</b>	W 7 ; W 9
<b>SLR (MM)</b>	475	<b>ECE</b>	E4-106R-000638
<b>RC (MM)</b>	3104	<b>SRI</b>	500

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	570	660	755	845	940	1030
40	570	660	755	845	940	1030
30	610	710	810	910	1010	1105
10 LT	765	890	1015	1140	1265	1385
10 HT	610	710	810	910	1010	1105

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.