

EARTHMAX SR 30



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 30



EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
						REC RIM	ALT RIM							
														
Ø25"	17.5 R 25	TL	E3/L3	**/*	167 B 176 A2	14.00/1.5	-	150	446	1347	606	4021	29	CR
	20.5 R 25	TL	L3	**	193 A2	17.00/2.0	17.00/1.7	0	529	1487	663	4439	32	CR
	26.5 R 25	TL	E3/L3	**/*	193 B 202 A2	22.00/3.0	-	230	689	1742	766	5200	38	CR
	26.5 R 25	TL	E3	**	193 B	22.00/3.0	-	230	689	1742	766	5200	38	CR
	15.5 R 25	TL	E3/L3	**/*	160 B 169 A2	12.00/1.3	-	130	397	1276	574	3809	27	CR


CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
			
			
B	208 kg		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH	O.W. (mm)	OD (mm)	SLR (mm)	RC (mm)	THREAD DEPTH	VERSION
					REC RIM	ALT RIM							
													
29.5 R 25	TL	L3	*	208 A2	25.00/3.5	-	0	765	1861	818	5555	42	CR
29.5 R 25	TL	E3/L3	**/*	200 B 208 A2	25.00/3.5	-	270	765	1861	818	5555	42	CR
23.5 R 25	TL	E3/L3	**/*	185 B 195 A2	19.50/2.5	-	200	612	1607	711	4797	34	CR
20.5 R 25	TL	E3/L3	**/*	177 B 186 A2	17.00/2.0	17.00/1.7	170	529	1487	663	4439	32	CR
26.5 R 25	TL	L3	*	202 A2	22.00/3.0	-	0	689	1742	766	5200	38	CR
29.5 R 25	TL	E3	**	200 B	25.00/3.5	-	270	765	1861	818	5555	42	CR
17.5 R 25	TL	L3	***	188 A2	14.00/1.5	-	0	446	1347	606	4021	29	CR

CR: CUT RESISTANT COMPOUND

TECHNOLOGIES		PERFORMANCES	
 E3/L3	 208 kg		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index