


FL 639

TIRE SIZE	560/45 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	STREUMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	152 D ; 163 A8



ABMESSUNGEN US STANDARD

USA-CODE	94034260	RC (IN)	130.0
SW (IN)	21.4	RIM REC	AG 16.00
OD (IN)	42.4	ECE	E4-106R-000627
SLR (IN)	19.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2290	2650	3000	3570	4210	4780	5360	6000	6570	7130
40	2510	2910	3300	3950	4620	5250	5950	6530	7210	7830
30	3040	3520	3990	4740	5600	6390	7140	7970	8730	9480
25	3440	3980	4520	5400	6350	7210	8100	9020	9890	10750
15	3970	4590	5200	6220	7300	8320	9330	10360	11390	12370
5	4510	5210	5920	7050	8320	9480	10630	11790	12960	14090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.