


# AIROMAX AM 543

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>445/95 R 25</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | GUINDASTE MÓVEL  |
| <b>VERSÃO</b>       | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 177 E  |



## DIMENSÕES IS STANDARD

|                 |           |                |                            |
|-----------------|-----------|----------------|----------------------------|
| <b>OD (MM)</b>  | 1480      | <b>RIM ALT</b> | 11.00/1.7 CR; 11.00/1.7CRL |
| <b>SLR (MM)</b> | 670       |                |                            |
| <b>RC (MM)</b>  | 4502      |                |                            |
| <b>RIM REC</b>  | 11.25/2.0 |                |                            |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>9.00</b> |
|-------------------|-------------|
| 30                | 9500        |
| 40                | 9000        |
| 50                | 8500        |
| 60                | 8175        |
| 70                | 7300        |
| 80                | 6000        |
| 90                | 5150        |
| 100               | 4375        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.