


# FL 630 SUPER

<b>TIRE SIZE</b>	<b>600/55 R 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPARGITORE / AUTOBOTTE / RIMORCHIO / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	162 D



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	595	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1232	<b>ECE</b>	E11-106R-004759
<b>SLR (MM)</b>	560	<b>SRI</b>	575
<b>RC (MM)</b>	3757		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1580	1775	2210	2510	2900	3290	3590	3940	4325
65	1735	1950	2425	2755	3185	3610	3945	4325	4750
50	2100	2360	2935	3335	3855	4370	4775	5235	5750
40	2360	2650	3295	3750	4330	4910	5365	5880	6460
25	2740	3080	3830	4355	5030	5705	6230	6830	7505
10	3125	3510	4365	4960	5730	6500	7100	7785	8550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.