

# AGRIMAX RT 600

<b>TIRE SIZE</b>	<b>650/75 R 32</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	HARVESTER / SPREADER / TRACTOR / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	172 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94055968	<b>RC (IN)</b>	213.2
<b>SW (IN)</b>	25.8	<b>RIM REC</b>	DW 21 B
<b>OD (IN)</b>	70.4	<b>RIM ALT</b>	DW 20 B ; DW 23 B
<b>SLR (IN)</b>	31.8	<b>ECE</b>	E11-106R-004755

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46	49	55
30	6390	7360	9030	9870	10840	11810	12790	13890	-	-
25	6390	7360	9030	9870	10840	11810	12790	13890	-	-
20	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 LT	8560	9880	12100	13230	14530	15830	17130	18620	-	-
5 HT	6840	7880	9670	10560	11610	12640	13690	14870	-	-
5 CYC.	-	10520	13460	14760	17120	18770	20550	22320	22670	23610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.