

# AS 504

**4.00 - 16****UM** US STANDARD**CONSTRUCTION**  BIAS**MACHINERY** TELESKOPIK YÜKLEYİCİ / TARLA  
RÖMORKU / UYGULAMALI MAKİNE /  
TELESKOPIK YÜKLEYİCİ**VERSION** STANDARD**TIRE TYPE** TT

66 A8

78 A8



## UNDEFINED US STANDARD

<b>USA CODE</b>	94056576	<b>RC (IN)</b>	76.2
<b>SW (IN)</b>	4.3	<b>RIM REC</b>	3.00 D
<b>OD (IN)</b>	24.7	<b>RIM ALT</b>	2.50 C
<b>SLR (IN)</b>	11.7	<b>ECE</b>	E11-106R-005193

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>41</b>
<b>5 FR</b>	1310
<b>15 FR</b>	1110
<b>20 FR</b>	1050
<b>25 FR</b>	940
<b>5 DW</b>	930
<b>15 DW</b>	780
<b>20 DW</b>	740
<b>25 DW</b>	660

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.