

# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>520/70 R 34</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	IRRORAZIONE / TRATTORE / VENDEMMIATRICE / MIETITREBBIA / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 D



## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94063079	<b>RC (IN)</b>	194.0
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	W 16 L
<b>OD (IN)</b>	64.6	<b>RIM ALT</b>	W 15 L; W 18 L
<b>SLR (IN)</b>	29.1	<b>ECE</b>	E11-106R-005831

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	3820	4450	5070	5700	6330	6940
30	4020	4670	5330	5990	6920	7300
25	4190	4870	5560	6240	6920	7610
20	4400	5110	5840	6560	7270	7990
5 LT	5130	5960	6800	7640	8480	9310
5 HT	4400	5110	5840	6560	7270	7990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.