



PRINTED ON  
22-04-2026

## DATA SHEET

# GR 288

|                     |                |
|---------------------|----------------|
| <b>TYRE SIZE</b>    | 20.5 - 25      |
| <b>UM</b>           | US STANDARD    |
| <b>CONSTRUCTION</b> | ⊗ BIAS         |
| <b>MACHINERY</b>    | LOADER / DOZER |
| <b>VERSION</b>      | STANDARD       |
| <b>TYRE TYPE</b>    | TL             |



### DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94014446 | <b>RIM REC</b> | 17.00/2.0       |
| <b>OD (IN)</b>  | 58.3     | <b>RIM ALT</b> | 17.00/1.7       |
| <b>SLR (IN)</b> | 25.8     | <b>ECE</b>     | E11-106R-005405 |
| <b>RC (IN)</b>  | 173.1    | <b>PR</b>      | 16              |

### LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 33   | 51    |
|-----------|------|-------|
| 25        | 8800 | -     |
| 5         | -    | 18200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.