


# AGRIMAX RT 765

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>520/70 R 38</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |  RADIAL            |
| <b>MACHINERY</b>    | PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
| <b>LI/SS</b>        | 150 D   |



## DIMENSIUNI IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 516  | <b>RIM REC</b> | W 16 L          |
| <b>OD (MM)</b>  | 1749 | <b>RIM ALT</b> | W 15 L; W 18 L  |
| <b>SLR (MM)</b> | 793  | <b>ECE</b>     | E11-106R-005525 |
| <b>RC (MM)</b>  | 5300 | <b>SRI</b>     | 825             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 65         | 1845 | 2145 | 2450 | 2750 | 3050 | 3350 |
| 50         | 1940 | 2255 | 2570 | 2890 | 3205 | 3520 |
| 40         | 2020 | 2350 | 2680 | 3010 | 3340 | 3670 |
| 30         | 2125 | 2470 | 2815 | 3165 | 3510 | 3855 |
| 10 LT      | 2470 | 2875 | 3280 | 3685 | 4090 | 4490 |
| 10 HT      | 2125 | 2470 | 2815 | 3165 | 3510 | 3855 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.