

# TF 9090

|                     |                                      |
|---------------------|--------------------------------------|
| <b>TIRE SIZE</b>    | <b>6.00 - 16</b>                     |
| <b>UM</b>           | IS STANDARD                          |
| <b>CONSTRUCTION</b> | ⊠ BIAS                               |
| <b>MACHINERY</b>    | TRATTORINO / TRATTORE /<br>RIMORCHIO |
| <b>VERSIONE</b>     | STANDARD                             |
| <b>TIRE TYPE</b>    | TT                                   |
| <b>LI/SS</b>        | 94 A6                                |



## DIMENSIONI IS STANDARD

|                 |      |                |                     |
|-----------------|------|----------------|---------------------|
| <b>SW (MM)</b>  | 170  | <b>RIM REC</b> | 4,50 E              |
| <b>OD (MM)</b>  | 735  | <b>RIM ALT</b> | 4.00 E; 5 K; 5.00 F |
| <b>SLR (MM)</b> | 346  | <b>ECE</b>     | E4-106R-001961      |
| <b>RC (MM)</b>  | 2190 | <b>PR</b>      | 8                   |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.50</b> |
| 30                | 670         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.