


AGRIMAX V- FLECTO

| | |
|---------------------|--|
| TIRE SIZE | VF 900/65 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР ВЫСОКОЙ МОЩНОСТИ / ТРАКТОР-ТЯГАЧ |
| VERSION | STEEL BELTED SPL |
| TIRE TYPE | TL |
| LI/SS | 193 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 900 | RIM REC | DW 30B |
| OD (MM) | 2338 | ECE | E11-106R-0010524 |
| SLR (MM) | 1006 | SRI | 1100 |
| RC (MM) | 7003 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 |
|---------------|------|-------|-------|-------|-------|-------|-------|
| 70 | 5335 | 6170 | 7010 | 7950 | 8685 | 9415 | 10465 |
| FROM 65 TO 40 | 5865 | 6785 | 7705 | 8740 | 9545 | 10350 | 11500 |
| 30 | 5980 | 6920 | 7855 | 8910 | 9735 | 10555 | 11730 |
| 20 | 6095 | 7055 | 8010 | 9085 | 9925 | 10760 | 11960 |
| 10 | 6450 | 7460 | 8475 | 9610 | 10495 | 11385 | 12650 |
| UPTO 30 CYC | 6655 | 7695 | 8740 | 9915 | 10830 | 11745 | 13050 |
| UPTO 15 CYC | 7945 | 9190 | 10435 | 11840 | 12930 | 14020 | 15580 |
| UPTO 10 CYC | 8705 | 10070 | 11440 | 12975 | 14170 | 15365 | 17075 |
| 10HT | 5980 | 6920 | 7855 | 8910 | 9735 | 10555 | 11730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.