


# AGRIMAX FORCE



<b>TIRE SIZE</b>	<b>IF 480/95 R 50</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 D

## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 B
<b>OD (MM)</b>	2170	<b>ECE</b>	E11-106R-004898
<b>SLR (MM)</b>	1002	<b>SRI</b>	1025
<b>RC (MM)</b>	6574	<b>TRA CODE</b>	R1W

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2565	2945	3385	3820	4255	4695	5130	5460
<b>FROM 65 TO 40</b>	2820	3240	3720	4200	4680	5160	5640	6000
30	2930	3365	3865	4365	4865	5365	5865	6240
20	3045	3495	4015	4535	5050	5570	6090	6480
10	3580	4110	4720	5330	5940	6550	7160	7620
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3945	4535	5205	5880	6550	7220	7895	8400
10HT	2930	3365	3865	4365	4865	5365	5865	6240

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.