

# AGRIMAX RT 855

**250/80 R 18****UM** US STANDARD**CONSTRUCTION**  RADIAL**MACHINERY** İLAÇLAMA / ÜZÜM HASAT MAKİNESİ /  
TRAKTÖR / BIÇERDÖVER /  
UYGULAMALI MAKİNE**VERSION** STANDARD**TIRE TYPE** TL

125 A8 ; 125 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94066131	<b>RC (IN)</b>	100.0
<b>SW (IN)</b>	9.8	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	32.9	<b>RIM ALT</b>	W 7 ; W 9
<b>SLR (IN)</b>	14.8	<b>ECE</b>	E11-106R-006605

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	57	52	58
30	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	3460	3640
25	1280	1500	1720	1930	2150	2340	2590	2730	2990	3240	2460	3640
20	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900
5 LT	1720	2010	2300	2590	2890	3130	3470	3670	4010	4350	4640	4880
5 HT	1370	1610	1840	2070	2300	2500	2780	2930	3210	3480	3710	3900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.