

# AGRIMAX FORCE

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | IF 600/70 R 30 CFO                                                                       |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | MOISSONNEUSE / TRACTEUR DE<br>FORTE PUISSANCE / TRACTEUR                                 |
| VERSION      | STANDARD                                                                                 |
| TIRE TYPE    | TL                                                                                       |
| LI/SS        | 165 D                                                                                    |



## DIMENSIONS US STANDARD

|          |          |         |                   |
|----------|----------|---------|-------------------|
| CODE USA | 94045211 | RC (IN) | 189.0             |
| SW (IN)  | 23.7     | RIM REC | DW 21 B ; DW 21 A |
| OD (IN)  | 63.1     | RIM ALT | DW 20 A ; DW 20 B |
| SLR (IN) | 27.9     | ECE     | E11-106R-006495   |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI     | 9    | 12    | 15    | 17    | 20    | 23    | 29    | 35    |
|---------------|------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 4850 | 5570  | 6390  | 7230  | 8050  | 8870  | 9700  | 10330 |
| FROM 40 TO 25 | 5330 | 6130  | 7030  | 7950  | 8850  | 9750  | 10670 | 11400 |
| 20            | 5540 | 6370  | 7310  | 8260  | 9200  | 10140 | 11090 | 11810 |
| 12            | 5750 | 6610  | 7590  | 8580  | 9560  | 10530 | 11520 | 12260 |
| 5             | 6770 | 7780  | 8930  | 10090 | 11230 | 12380 | 13550 | 14420 |
| UPTO 20 CYC   | 6930 | 7960  | 9140  | 10330 | 11500 | 12680 | 13870 | 14760 |
| UPTO 10 CYC   | 8270 | 9490  | 10890 | 12310 | 13710 | 15110 | 16530 | 17590 |
| UPTO 5 CYC    | 9060 | 10420 | 11950 | 13500 | 15050 | 16580 | 18130 | 19300 |
| 5 HT          | 5540 | 6370  | 7300  | 8260  | 9200  | 10140 | 11090 | 11800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.