

# STAR TRAC

|                  |                                 |
|------------------|---------------------------------|
| <b>TIRE SIZE</b> | <b>DW 500/95 D 32</b>           |
| <b>UM</b>        | IS STANDARD                     |
| <b>MACHINERY</b> | COLHEDORA DE ALGODÃO / CEIFEIRA |
| <b>VERSÃO</b>    | STANDARD                        |
| <b>TIRE TYPE</b> | TL                              |
| <b>LI/SS</b>     | 162 A8 ; 169 A5                 |



## DIMENSÕES IS STANDARD

|                 |      |                         |          |
|-----------------|------|-------------------------|----------|
| <b>SW (MM)</b>  | 500  | <b>RC (MM)</b>          | 5324     |
| <b>OD (MM)</b>  | 1836 | <b>RIM REC</b>          | 13.00 DW |
| <b>SLR (MM)</b> | 809  | <b>TREAD DEPTH (MM)</b> | 55,5     |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>1.70</b> |
|-------------------|-------------|
| 40                | 4750        |
| 25                | 5800        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.