

# AW 708

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	148 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94010257	<b>RC (IN)</b>	99.8
<b>SW (IN)</b>	18.5	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	34.1	<b>ECE</b>	E4-106R-002268
<b>SLR (IN)</b>	15.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>48</b>
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.